

<b>Vlonderplanken specificaties</b>	<b>ProDeck™ vlonderplank 21 mm dik 14,5 cm breed</b>	<b>ProDeck™ vlonderplank 21 mm dik 15 cm breed</b>	<b>ProDeck™ vlonderplank 25 mm dik 15 cm breed</b>	<b>ProDeck™ vlonderplank 25 mm dik 24 cm breed</b>	<b>WoodPlastic® vlonderplank max forest 19,5 cm breed</b>	<b>WoodPlastic® vlonderplank top 14 cm breed</b>	<b>WoodPlastic® vlonderplank step 16 cm breed</b>
Breedte* – in cm	14,5	15	15	24	19,5	13,5	16
Dikte – in mm	21	21	25	25	22	22	23
Naad met standaardclips – in mm	7	7	5	7	✘	✘	✘
Naad met Aslon-systeemclips – in mm	6	7	7	7	5	✘	5
Naad met rvs-clips – in mm	7	7	7	7	6	✘	6
Naad met TOP-clips – in mm	✘	✘	✘	✘	✘	3	✘
Holkamer uitvoering	✓	✓	✓	✓	✘	✘	✘
Massieve uitvoering	✘	✘	✘	✘	✓	✓	✓
<i>Privévlonder:</i> afstand onderbalken hart-op-hart – in cm	30	30	35	35	45	40	30
<i>Openbaar vlonder:</i> afstand onderbalken hart-op-hart – in cm	25	25	30	30	35	30	27,5
Aantal clips per m2 (advies)	23	23	21	12	15	20	21

\*Werkende breedte = breedte (in cm) + naad (in mm) van gebruikte clipsysteem